



SAFETY DATA SHEET

**HYL40 / HYL80 / HYL250 / HYL300 /
HYLOMAR M ALL GRADES (LIGHT,
MEDIUM AND HEAVY)**

Infosafe No.: LQ59Z
ISSUED Date : 08/02/2019
ISSUED by: NASON ENGINE PARTS

1. IDENTIFICATION

GHS Product Identifier

HYL40 / HYL80 / HYL250 / HYL300 / HYLOMAR M ALL GRADES (LIGHT, MEDIUM AND HEAVY)

Company Name

NASON ENGINE PARTS

Address

Unit 2/5 Monterey Road Dandenong South
Vic 3175 AUSTRALIA

Telephone/Fax Number

Tel: 9797 1140

Fax: 9794 0222

Emergency phone number

+61 1 800 686 951 (Australia) 24 hours

Access code: 333544

Recommended use of the chemical and restrictions on use

Non-Setting and Non-Hardening Gasketing Compound.

2. HAZARD IDENTIFICATION

GHS classification of the substance/mixture

Classified as Hazardous according to the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) including Work, Health and Safety Regulations, Australia.

Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Flammable Liquids: Category 2

Eye Damage/Irritation: Category 2A

STOT Single Exposure: Category 3 (narcotic)

Signal Word (s)

DANGER

Hazard Statement (s)

AUH066 Repeated exposure may cause skin dryness or cracking.

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Pictogram (s)

Flame, Exclamation mark



Precautionary statement – Prevention

- P210 Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash contaminated skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement – Response

- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 Call a POISON CENTER or doctor/physician if you feel unwell.
P337+P313 If eye irritation persists: Get medical advice/attention.
P370+P378 In case of fire: Use water spray, foam, dry chemical or carbon dioxide. for extinction.

Precautionary statement – Storage

- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Precautionary statement – Disposal

- P501 Dispose of contents/container to an approved waste disposal plant..

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients

Name	CAS	Proportion
Acetone	67-64-1	40-50 %
Silica	7631-86-9	10-20 %
Ingredients determined not to be hazardous		Balance

4. FIRST-AID MEASURES

Inhalation

If inhaled, remove affected person from contaminated area. Apply artificial respiration if not breathing. Seek medical attention.

Ingestion

Do not induce vomiting. Wash out mouth thoroughly with water. Seek immediate medical attention.

Skin

Remove all contaminated clothing immediately. Wash affected area thoroughly with soap and water. Wash contaminated clothing before reuse or discard. Seek medical attention.

Eye contact

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention.

First Aid Facilities

Eyewash, safety shower and normal washroom facilities.

Advice to Doctor

Treat symptomatically.

Other Information

For advice in an emergency, contact a Poisons Information Centre (Phone Australia 131 126) or a doctor at once.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water spray, foam, powder or carbon dioxide.

Unsuitable Extinguishing Media

Do not use water jet as an extinguisher, as this will spread the fire.

Hazards from Combustion Products

Under fire conditions this product may emit toxic and/or irritating fumes including carbon oxides.

Specific Hazards Arising From The Chemical

Highly flammable liquid and vapour. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create fire or explosion hazard.

Hazchem Code

3YE

Decomposition Temperature

Not available

Precautions in connection with Fire

Fire fighters should wear full protective clothing and self-contained breathing apparatus (SCBA) operated in positive pressure mode. In case of fire the product may be violently or explosively reactive. Use water spray to disperse vapours. This product should be prevented from entering drains and watercourses.

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures

Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations.

If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Wear appropriate personal protective equipment and clothing to prevent exposure. Handle and use the material in a well-ventilated area, away from sparks, flames and other ignition sources. Have emergency equipment (for fires, spills, leaks, etc.) readily available. Work from suitable, labelled, fire-resistant containers. Open containers carefully as they may be under pressure. Keep containers tightly closed. Flameproof equipment is necessary in areas where the product is being used. Take precautionary measures against static discharges. Earth or bond all equipment. Do not empty into drains. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands before eating, drinking, smoking or using the toilet facilities.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated area away from sources of ignition, oxidising agents, strong acids, foodstuffs, and clothing. Keep containers closed when not in use, securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. Ensure that storage conditions comply with applicable local and national regulations.

For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limit values

No exposure standards have been established for this material. However, the available exposure limits for ingredients are listed below:

Acetone

TWA: 500 ppm, 1185 mg/m³

STEL: 1000 ppm, 2375 mg/m³

Silica

TWA: 2 mg/m³

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

Source: Safe Work Australia

Biological Limit Values

Name: ACETONE

Determinant: Acetone in urine

Value: (50 mg/L)

Sampling time: End of shift

Notation: Ns

Source: American Conference of Industrial Hygienists (ACGIH)

Appropriate Engineering Controls

This substance is hazardous and should be used with a local exhaust ventilation system, drawing vapours away from workers' breathing zone. A flame-proof exhaust ventilation system is required. If the engineering controls are not sufficient to maintain concentrations of vapours/mists below the exposure standards, suitable respiratory protection must be worn. Refer to relevant regulations for further information concerning ventilation requirements.

Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NZS 60079.10.1 Explosive atmospheres - Classification of areas - Explosive gas atmospheres, for further information concerning ventilation requirements.

Respiratory Protection

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable vapor/mist filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements.

Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

Eye Protection

Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations.

Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 (series) - Eye Protectors for Industrial Applications.

Hand Protection

Wear gloves of impervious material such as butyl rubber. Breakthrough time >120 minutes. Be aware that the liquid may penetrate the gloves. Frequent change is advisable. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

Body Protection

Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

9. PHYSICAL AND CHEMICAL PROPERTIES

Properties	Description	Properties	Description
Form	Gel	Appearance	Blue thixotropic gel.
Colour	Blue	Odour	Sweet. Ethereal.
Decomposition Temperature	Not available	Melting Point	Not available
Boiling Point	Not available	Solubility in Water	Slightly miscible
pH	Not available	Vapour Pressure	185 mmHg (20°C)
Vapour Density (Air=1)	2 (Air=1)(20°C)	Evaporation Rate	Not available
Odour Threshold	Not available	Viscosity	Not available
Volatile Component	VOC: 25-50% (weight) (Hylomar Test Method 1.1A Determination of Volatile Matter)	Partition Coefficient: n- octanol/water	Acetone: -0.24
Flash Point	-17.0°C (Closed cup)	Flammability	Highly flammable
Auto-Ignition Temperature	Not available	Flammable Limits - Lower	4%
Flammable Limits - Upper	57%	Relative density	Light grade: 0.95 (20°C) Medium grade: 1.03 (20°C) Heavy grade: 1.10 (20°C)

10. STABILITY AND REACTIVITY

Chemical Stability

Stable under normal conditions of storage and handling. Risk of ignition.

Reactivity and Stability

Reacts with incompatible materials.

Conditions to Avoid

Heat, sparks, flames and other sources of ignition. Avoid temperatures exceeding the flash point.

Incompatible materials

Strong oxidising agents.

Hazardous Decomposition Products

Thermal decomposition may result in the release of toxic and/or irritating fumes including carbon oxides.

Possibility of hazardous reactions

Reacts with incompatible materials.

Hazardous Polymerization

Not available

11. TOXICOLOGICAL INFORMATION

Toxicology Information

No toxicity data available for this material. The available acute toxicity data for the ingredients is given below.

Acute Toxicity - Oral

Acetone

LD50 (Rat): 5,800 mg/kg

Silica

LD50 (Rat): >3,300 mg/kg

Acute Toxicity - Inhalation

Acetone

LC50 (Rat): 76 mg/l/4h (vapour)

Silica

LC50 (Rat): >0.14 mg/l/24h (dust)

Acute Toxicity - Dermal

Acetone

LD50 (Rabbit): >15,700 mg/kg/24h

Silica

LD50 (Rabbit): >5,00 mg/kg/24h

Ingestion

Ingestion of this product may irritate the gastric tract causing nausea and vomiting.

Inhalation

May cause irritation to the mucous membrane and upper airways, especially where vapours or mists are generated. Symptoms include sneezing, coughing, wheezing, shortness of breath, headache, dizziness, drowsiness, nausea and vomiting.

Skin

May be irritating to skin. The symptoms may include redness, itching and swelling.

Repeated exposure may cause skin dryness and cracking and may lead to dermatitis.

Eye

Causes serious eye irritation. On eye contact this product will cause tearing, stinging, blurred vision, and redness.

Respiratory sensitisation

Not expected to be a respiratory sensitiser.

Skin Sensitisation

Not expected to be a skin sensitiser.

Germ cell mutagenicity

Not considered to be a mutagenic hazard.

Carcinogenicity

Not considered to be a carcinogenic hazard.

Silica (amorphous) is listed as a Group 3: Not classifiable as to carcinogenicity to humans according to International Agency for Research on Cancer (IARC).

Reproductive Toxicity

Not considered to be toxic to reproduction.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Not expected to cause toxicity to a specific target organ through repeated or prolonged exposure.

Aspiration Hazard

Not expected to be an aspiration hazard.

12. ECOLOGICAL INFORMATION

Ecotoxicity

No ecological data available for this material. The available ecological data for the ingredients is given below:

Persistence and degradability

Not available

Mobility

Miscible in water. May spread in water systems.

Mobility in soil: The acetone component is miscible with water and may spread in water systems.

Bioaccumulative Potential

Acetone n-octanol/water (log Kow) : -0.24

Other Adverse Effects

The product contains a substance which has a photochemical ozone creation potential.

Environmental Protection

Do not discharge this material into waterways, drains and sewers.

Acute Toxicity - Fish

Acetone

Acute

LC50 (Pimephales promelas): 7,163 mg/l/96h

Acute Toxicity - Daphnia

Acetone

Acute

LC50 (Daphnia pulex): 8,800 mg/l/48h

chronic

NOEC (Daphnia magna): > 79 mg/l/21d

13. DISPOSAL CONSIDERATIONS

Disposal considerations

Dispose of waste according to applicable local and national regulations. Labels should not be removed from containers until they have been cleaned. Do not cut, puncture or weld on or near containers. Empty containers may contain flammable residues. Contaminated containers must not be treated as household waste. Containers should be cleaned by appropriate methods and then re-used or disposed of by landfill or incineration as appropriate. Do not incinerate closed containers. Advise flammable nature.

14. TRANSPORT INFORMATION

Transport Information

Road and Rail Transport (ADG7):

This material is Dangerous Goods Class 3 - Flammable Liquid according to The Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Class 3 - Flammable Liquids are incompatible in a placard load with any of the following:

- Class 1, Explosives
- Division 2.1, Flammable Gases, (Division 2.1 and Class 3 are incompatible in transport if both are in tanks or other receptacles with a capacity individually exceeding 500 L.)
- Division 2.3, Toxic Gases
- Division 4.2 Spontaneously Combustible Substances
- Division 5.1 Oxidising substances and Division 5.2, Organic Peroxides
- Class 6 Toxic or Infectious Substances (where the flammable liquid is nitromethane)
- Class 7 Radioactive Substances.

Marine Transport (IMO/IMDG):

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

UN-No: 1133

Proper Shipping Name: ADHESIVES

Class: 3

Packaging Group: II

EMS: F-E, S-D

Air Transport (ICAO/IATA):

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

UN-No: 1133

Proper Shipping Name: ADHESIVES

Class: 3

Packaging Group: II

Packaging Instructions (passenger & cargo): 353

Packaging Instructions (cargo): 364
Label: Flammable Liquid
Special provisions: A3

U.N. Number

1133

UN proper shipping name

ADHESIVES

Transport hazard class(es)

3

Packing Group

II

Hazchem Code

3YE

IERG Number

14

IMDG Marine pollutant

No

Transport in Bulk

Not applicable

Special Precautions for User

Not available

15. REGULATORY INFORMATION

Regulatory information

Classified as Hazardous according to the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) including Work, Health and Safety Regulations, Australia.

Classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Poisons Schedule

S5

16. OTHER INFORMATION

Date of preparation or last revision of SDS

SDS amendment February 2021

1. Identification

SDS Reviewed: February 2019

Supersedes: December 2018

References

Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.

Standard for the Uniform Scheduling of Medicines and Poisons.

Australian Code for the Transport of Dangerous Goods by Road & Rail.

Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.

Workplace exposure standards for airborne contaminants.

Adopted biological exposure determinants, American Conference of Industrial Hygienists (ACGIH).

Globally Harmonised System of Classification and Labelling of Chemicals.

END OF SDS

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

The compilation of SDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.
Copying of any SDS displayed is permitted for personal use only and otherwise is not permitted. In particular the SDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of SDS without the express written consent of Chemical Safety International Pty Ltd.