

Safety Data Sheet

according to WHS Regulations

Date of issue: 04.08.2026

Revised On: 04.08.2026

SECTION 1: Identification

Trade name: PLASTA WRAP CLEAR

Article number: 0000162411

Sector of Use SU21 Consumer uses: Private households / general public / consumers

Product category PC9a Paints and coatings.

Company Name: Nason Engine Parts

Address: Unit 2/5 Monterey Road Dandenong South Vic 3175 AUSTRALIA

Telephone/Fax number: Tel: 03 9797 1140

Emergency telephone number: Australia: 1300 954 583

SECTION 2: Hazard(s) Identification

2.1 Classification of the substance or mixture

Additional information:

Hazard pictograms



GHS02 GHS07 GHS08

Signal word

Danger

Hazard-determining components of labelling:

VM&P Naphtha (25-50 %)

n-butane (10-15 %)

Stoddard Solvent (0.2-1 %)

Naphtha, hydrotreated heavy (0.2-1 %)

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

H315 Causes skin irritation.

H340 May cause genetic defects.

H350 May cause cancer.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P201 Obtain special instructions before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P264 Wash thoroughly after handling.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 3: Composition and Information on Ingredients

3.2 Chemical characterisation: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

64742-89-8	VM&P Naphtha	25-50%
	Flammable liquids – Category 2, H225; Germ cell mutagenicity – Category 1B, H340; Carcinogenicity – Category 1B, H350; Aspiration hazard – Category 1, H304	
74-98-6	propane	15-25%
	Flammable gases – Category 1A, H220	
106-97-8	n-butane	10-15%
	Flammable gases – Category 1A, H220; Germ cell mutagenicity – Category 1A, H340; Carcinogenicity – Category 1A, H350	
142-82-5	heptane	10-15%
	Flammable liquids – Category 2, H225; Aspiration hazard – Category 1, H304; Aquatic Chronic 1, H410; Skin corrosion/irritation – Category 2, H315; Specific target organ toxicity (single exposure) – Category 3, H336	
1330-20-7	xylene (mix)	≥5-<10%
	Flammable liquids – Category 3, H226; Acute toxicity - dermal – Category 4, H312; Acute toxicity - inhalation – Category 4, H332; Skin corrosion/irritation – Category 2, H315; Specific target organ toxicity (single exposure) – Category 3, H335	
78-93-3	methyl ethyl ketone	1-5%
	Flammable liquids – Category 2, H225; Eye damage/irritation – Category 2A, H319; Specific target organ toxicity (single exposure) – Category 3, H335-H336	
110-43-0	methyl amyl ketone	1-5%
	Flammable liquids – Category 3, H226; Acute toxicity - oral – Category 4, H302; Acute toxicity - inhalation – Category 4, H332	
100-41-4	ethyl benzene	1-5%
	Flammable liquids – Category 2, H225; Aspiration hazard – Category 1, H304; Acute toxicity - inhalation – Category 4, H332; Skin corrosion/irritation – Category 2, H315; Eye damage/irritation – Category 2A, H319	

(Contd. on page 2)

Safety Data Sheet

according to WHS Regulations

Date of issue: 04.08.2026

Revised On: 04.08.2026

Trade name: PLASTA WRAP CLEAR

(Contd. of page 1)

8052-41-3	Stoddard Solvent Flammable liquids – Category 3, H226; Germ cell mutagenicity – Category 1B, H340; Carcinogenicity – Category 1B, H350; Aspiration hazard – Category 1, H304	0.2-1%
64742-48-9	Naphtha, hydrotreated heavy Germ cell mutagenicity – Category 1B, H340; Carcinogenicity – Category 1B, H350; Aspiration hazard – Category 1, H304; Flammable liquids – Category 4, H227	0.2-1%
64742-95-6	Solvent naphtha, light aromatic Flammable liquids – Category 3, H226; Germ cell mutagenicity – Category 1B, H340; Carcinogenicity – Category 1B, H350; Aspiration hazard – Category 1, H304	0.19%

SECTION 4: First Aid Measures

4.2 Most important symptoms and effects, both acute and delayed

After inhalation:

After skin contact:

After eye contact:

After swallowing:

4.3 Indication of any immediate medical attention and special treatment needed

Dizziness

Supply fresh air; consult doctor in case of complaints.

Generally the product does not irritate the skin.

Rinse opened eye for several minutes under running water.

Do not induce vomiting; call for medical help immediately.

No further relevant information available.

SECTION 5: Fire Fighting Measures

5.1 Extinguishing media

Extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray.

5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

5.3 Advice for firefighters

Protective equipment:

Mount respiratory protective device.

Additional information

Cool endangered receptacles with water spray.

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Use respiratory protective device against the effects of fumes/dust/aerosol.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

6.3 Methods and material for containment and cleaning up:

Absorb liquid components with liquid-binding material.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Fire/explosion protection:

Use only in well ventilated areas.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

7.2 Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and receptacles:

Suitable material for receptacles and pipes: steel or stainless steel.

Information about storage in one common storage facility:

Not available.

7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls and personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

74-98-6 propane

WES Asphyxiant

106-97-8 n-butane

WES Long-term value: 1900 mg/m³, 800 ppm

142-82-5 heptane

WES Short-term value: 2050 mg/m³, 500 ppmLong-term value: 1640 mg/m³, 400 ppm

1330-20-7 xylene (mix)

WES Short-term value: 655 mg/m³, 150 ppmLong-term value: 350 mg/m³, 80 ppm

(Contd. on page 3)

Safety Data Sheet

according to WHS Regulations

Date of issue: 04.08.2026

Revised On: 04.08.2026

Trade name: PLASTA WRAP CLEAR

(Contd. of page 2)

78-93-3 methyl ethyl ketone

WES Short-term value: 890 mg/m³, 300 ppm
Long-term value: 445 mg/m³, 150 ppm

110-43-0 methyl amyl ketone

WES Long-term value: 233 mg/m³, 50 ppm

100-41-4 ethyl benzene

WES Short-term value: 543 mg/m³, 125 ppm
Long-term value: 434 mg/m³, 100 ppm

8052-41-3 Stoddard Solvent

WES Long-term value: 790 mg/m³

8.2 Exposure controls**General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the skin.
Avoid contact with the eyes and skin.
Do not eat or drink while working.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:

Protective gloves
Neoprene gloves
The glove material has to be impermeable and resistant to the product.

Eye protection:

Tightly sealed goggles

SECTION 9: Physical and Chemical Properties**9.2 Other information****General Information**

Appearance: Aerosol.
Odour: Aromatic
Odour threshold: Not determined.
pH-value: Not determined.
Melting point/freezing point: Undetermined.
Initial boiling point and boiling range: 79 °C
Flash point: -19 °C
Flammability: Extremely flammable.
Auto-ignition temperature: 215 °C
Decomposition temperature: Not determined.
Ignition temperature: Product is not selfigniting.
Explosive properties: In use, may form flammable/explosive vapour-air mixture.
Lower: 1.1 Vol %
Upper: 10.9 Vol %
Vapour pressure: Not determined.
Density at 20 °C: 0.7 g/cm³
Relative density: Not determined.
Vapour density: Not determined.
Evaporation rate: Not applicable.
Solubility: Fully miscible.
Partition coefficient: n-octanol/water: Not determined.
Viscosity: Not determined.
Dynamic: Not determined.
Kinematic: Not determined.
Particle characteristics: Not applicable.
Physical state: Aerosol

SECTION 10: Stability and Reactivity**10.3 Possibility of hazardous reactions**

No dangerous reactions known.

Thermal decomposition / conditions to be avoided:

Stable at environment temperature.

10.4 Conditions to avoid

No further relevant information available.

10.5 Incompatible materials:

No further relevant information available.

10.6 Hazardous decomposition products:

No dangerous decomposition products known.

SECTION 11: Toxicological Information**Acute toxicity---**

Based on available data, the classification criteria are not met.

(Contd. on page 4)

Safety Data Sheet

according to WHS Regulations

Date of issue: 04.08.2026

Revised On: 04.08.2026

Trade name: PLASTA WRAP CLEAR

(Contd. of page 3)

LD/LC50 values relevant for classification:**1330-20-7 xylene (mix)**

Oral	LD50	8,700 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	6,350 mg/l (rat)

78-93-3 methyl ethyl ketone

Oral	LD50	3,300 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (rabbit)

100-41-4 ethyl benzene

Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	17,800 mg/kg (rabbit)

64742-48-9 Naphtha, hydrotreated heavy

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>3,000 mg/kg (rab)

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

May cause genetic defects.

Carcinogenicity

May cause cancer.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological Information**12.2 Persistence and degradability**

The product is biodegradable after prolonged adaptation.

Aquatic toxicity:

No further relevant information available.

12.3 Bioaccumulative potential

No further relevant information available.

12.4 Mobility in soil

No further relevant information available.

Remark:

Toxic for fish

General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Uncleaned packaging:****Recommendation:**

Disposal must be made according to official regulations.

Recommended cleansing agents:

Water, if necessary together with cleansing agents.

SECTION 14: Transport information**14.1 UN-Number**

UN1950

ADG, IMDG, IATA

UN1950

14.2 UN proper shipping name

ADG 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS

14.3 Transport hazard class(es)

Class 2 5F Gases.

Label

2.1

IMDG**Class**

2.1 Gases.

IATA**Class**

2.1 Gases.

Label

2.1

14.4 Packing group**ADG, IMDG, IATA**

Void

14.5 Environmental hazards:**Marine pollutant:**

Yes

Special marking (ADG):

Symbol (fish and tree)

Symbol (fish and tree)

14.6 Special precautions for user

Warning: Gases.

Hazard identification number (Kemler code):

-

EMS Number:

F-D,S-U

(Contd. on page 5)

Safety Data Sheet

according to WHS Regulations

Date of issue: 04.08.2026

Revised On: 04.08.2026

Trade name: PLASTA WRAP CLEAR

(Contd. of page 4)

Stowage Code

SW1 Protected from sources of heat.
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A.
For AEROSOLS with a capacity above 1 litre: Category B. For WASTE
AEROSOLS: Category C, Clear of living quarters.

Segregation Code

SG69 For AEROSOLS with a maximum capacity of 1 litre:
Segregation as for class 9. Stow "separated from" class 1 except for
division 1.4.
For AEROSOLS with a capacity above 1 litre:
Segregation as for the appropriate subdivision of class 2.
For WASTE AEROSOLS:
Segregation as for the appropriate subdivision of class 2.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

Transport/Additional information:**ADG**

Limited quantities (LQ)
Excepted quantities (EQ)

1L
Code: E0
Not permitted as Excepted Quantity

Transport category
Tunnel restriction code

2
D

IMDG

Limited quantities (LQ)
Excepted quantities (EQ)

1L
Code: E0
Not permitted as Excepted Quantity

UN "Model Regulation":

UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****Australian Inventory of Industrial Chemicals**

64742-89-8	VM&P Naphtha
74-98-6	propane
106-97-8	n-butane
142-82-5	heptane
1330-20-7	xylene (mix)
78-93-3	methyl ethyl ketone
110-43-0	methyl amyl ketone
100-41-4	ethyl benzene
69430-35-9	EASTOTAC D-130R
8052-41-3	Stoddard Solvent
64742-48-9	Naphtha, hydrotreated heavy
64742-95-6	Solvent naphtha, light aromatic
64-17-5	ethyl alcohol
55349-01-4	Polyamide Wax
	Bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate
	TINUVIN 1130
95-63-6	1,2,4 trimethylbenzene

Standard for the Uniform Scheduling of Medicines and Poisons

1330-20-7	xylene (mix)	S6
78-93-3	methyl ethyl ketone	S5

Australia: Priority Existing Chemicals

None of the ingredients is listed.

Directive 2012/18/EU**Named dangerous substances - ANNEX I****Seveso category**

None of the ingredients is listed.
P3a FLAMMABLE AEROSOLS
E2 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the application of lower-tier requirements

150 t

Qualifying quantity (tonnes) for the application of upper-tier requirements

500 t

Class	Share in %
NK	75.3

Waterhazard class:

Water hazard class 2 (Self-assessment): hazardous for water.

(Contd. on page 6)

Safety Data Sheet
according to WHS Regulations

Date of issue: 04.08.2026

Revised On: 04.08.2026

Trade name: PLASTA WRAP CLEAR

(Contd. of page 5)

SECTION 16: Other information**Department issuing SDS:** Technical Services