

Safety Data Sheet

according to WHS Regulations

Date of issue: 03.08.2026

Revised On: 03.08.2026

SECTION 1: Identification

Trade name: 46-115 GLOSS BLACK
Article number: EG00460115
Sector of Use SU21 Consumer uses: Private households / general public / consumers
Product category PC9a Paints and coatings.

Company Name: Nason Engine Parts
Address: Unit 2/5 Monterey Road Dandenong South Vic 3175 AUSTRALIA
Telephone/Fax number: Tel: 03 9797 1140

Emergency telephone number: Australia: 1300 954 583

SECTION 2: Hazard(s) Identification

2.1 Classification of the substance or mixture

Additional information:

Hazard pictograms



GHS02 GHS07 GHS08

Signal word

Danger

Hazard-determining components of labelling:

n-butane (5-10 %)
 Acetone (25-50 %)
 methyl isobutyl ketone (1-5 %)

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.
 H319 Causes serious eye irritation.
 H340 May cause genetic defects.
 H350 May cause cancer.
 H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P103 Read label before use.
 P201 Obtain special instructions before use.
 P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Pressurized container: Do not pierce or burn, even after use.
 P264 Wash thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear eye protection / face protection.
 P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P312 Call a POISON CENTER/doctor if you feel unwell.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P405 Store locked up.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 3: Composition and Information on Ingredients

3.2 Chemical characterisation: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

67-64-1	Acetone Flammable liquids – Category 2, H225; Eye damage/irritation – Category 2A, H319; Specific target organ toxicity (single exposure) – Category 3, H336 Specific concentration limit: Specific target organ toxicity (single exposure) – Category 3; H336: C ≥ 10 %	25-50%
74-98-6	propane Flammable gases – Category 1A, H220	15-25%
110-19-0	Isobutyl Acetate Flammable liquids – Category 2, H225	10-15%
106-97-8	n-butane Flammable gases – Category 1A, H220; Germ cell mutagenicity – Category 1A, H340; Carcinogenicity – Category 1A, H350	5-10%
2807-30-9	Glycol Ether EP Flammable liquids – Category 3, H226; Acute toxicity - dermal – Category 4, H312; Eye damage/irritation – Category 2A, H319	≥5-<10%
108-10-1	methyl isobutyl ketone Flammable liquids – Category 2, H225; Carcinogenicity – Category 2, H351; Acute toxicity - inhalation – Category 4, H332; Eye damage/irritation – Category 2A, H319; Specific target organ toxicity (single exposure) – Category 3, H335	1-5%

(Contd. on page 2)

Safety Data Sheet

according to WHS Regulations

Date of issue: 03.08.2026

Revised On: 03.08.2026

Trade name: 46-115 GLOSS BLACK

(Contd. of page 1)

108-65-6	PM acetate Flammable liquids – Category 3, H226	1-5%
107-87-9	Methyl Propyl Ketone Flammable liquids – Category 2, H225	1-5%

SECTION 4: First Aid Measures

4.2 Most important symptoms and effects, both acute and delayed

After inhalation:

After skin contact:

After eye contact:

After swallowing:

Dizziness

Supply fresh air; consult doctor in case of complaints.

Generally the product does not irritate the skin.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Fire Fighting Measures

5.1 Extinguishing media

Extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray.

5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

5.3 Advice for firefighters

Protective equipment:

Mount respiratory protective device.

Additional information

Cool endangered receptacles with water spray.

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Use only in well ventilated areas.

Fire/explosion protection:

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

7.2 Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and receptacles:

Suitable material for receptacles and pipes: steel or stainless steel.

Information about storage in one common storage facility:

Not available.

7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls and personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

67-64-1 Acetone

WES Short-term value: 2375 mg/m³, 1000 ppm
Long-term value: 1185 mg/m³, 500 ppm

74-98-6 propane

WES Asphyxiant

110-19-0 Isobutyl Acetate

WES Long-term value: 713 mg/m³, 150 ppm

106-97-8 n-butane

WES Long-term value: 1900 mg/m³, 800 ppm

108-10-1 methyl isobutyl ketone

WES Short-term value: 307 mg/m³, 75 ppm
Long-term value: 205 mg/m³, 50 ppm

108-65-6 PM acetate

WES Short-term value: 548 mg/m³, 100 ppm
Long-term value: 274 mg/m³, 50 ppm
Sk

(Contd. on page 3)

Safety Data Sheet

according to WHS Regulations

Date of issue: 03.08.2026

Revised On: 03.08.2026

Trade name: 46-115 GLOSS BLACK

(Contd. of page 2)

107-87-9 Methyl Propyl Ketone

WES Short-term value: 881 mg/m³, 250 ppm
Long-term value: 705 mg/m³, 200 ppm

8.2 Exposure controls**General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
Do not eat or drink while working.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:

Protective gloves
Neoprene gloves
The glove material has to be impermeable and resistant to the product.

Eye protection:

Tightly sealed goggles

SECTION 9: Physical and Chemical Properties**9.2 Other information****General Information**

Appearance: Aerosol.
Odour: Aromatic
Odour threshold: Not determined.
pH-value: Not determined.
Melting point/freezing point: Undetermined.
Initial boiling point and boiling range: -110 °C
Flash point: -19 °C
Flammability: Extremely flammable.
Auto-ignition temperature: 230 °C
Decomposition temperature: Not determined.
Ignition temperature: Product is not selfigniting.
Explosive properties: In use, may form flammable/explosive vapour-air mixture.
Lower: 1.7 Vol %
Upper: 10.9 Vol %
Vapour pressure: Not determined.
Density at 20 °C: 0.8 g/cm³
Relative density: Not determined.
Vapour density: Not determined.
Evaporation rate: Not applicable.
Solubility: Fully miscible.
Partition coefficient: n-octanol/water: Not determined.
Viscosity: Not determined.
Dynamic: Not determined.
Kinematic: Not determined.
Water: 0.0 %
Particle characteristics: Not applicable.
Physical state: Aerosol

SECTION 10: Stability and Reactivity**10.3 Possibility of hazardous reactions**

No dangerous reactions known.

Thermal decomposition / conditions to be avoided:

Stable at environment temperature.

10.4 Conditions to avoid

No further relevant information available.

10.5 Incompatible materials:

No further relevant information available.

10.6 Hazardous decomposition products:

No dangerous decomposition products known.

SECTION 11: Toxicological Information**Acute toxicity---**

Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:**110-19-0 Isobutyl Acetate**

Oral	LD50	4,763 mg/kg (rabbit)
------	------	----------------------

108-10-1 methyl isobutyl ketone

Oral	LD50	2,100 mg/kg (rat)
Dermal	LD50	16,000 mg/kg (rab)
Inhalative	LC50/4 h	11 mg/l (ATE)
		8.3-16.6 mg/l (rat)

(Contd. on page 4)

Safety Data Sheet

according to WHS Regulations

Date of issue: 03.08.2026

Revised On: 03.08.2026

Trade name: 46-115 GLOSS BLACK

(Contd. of page 3)

108-65-6 PM acetate

Oral	LD50	8,500 mg/kg (rat)
Inhalative	LC50/4 h	35.7 mg/l (rat)

Skin corrosion/irritation	Based on available data, the classification criteria are not met.
Serious eye damage/irritation	Causes serious eye irritation.
Respiratory or skin sensitisation	Based on available data, the classification criteria are not met.
Germ cell mutagenicity	May cause genetic defects.
Carcinogenicity	May cause cancer.
Reproductive toxicity	Based on available data, the classification criteria are not met.
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met.

SECTION 12: Ecological Information

12.2 Persistence and degradability	The product is biodegradable after prolonged adaptation.
Aquatic toxicity:	No further relevant information available.
12.3 Bioaccumulative potential	No further relevant information available.
12.4 Mobility in soil	No further relevant information available.
General notes:	Danger to drinking water if even extremely small quantities leak into the ground. Danger to drinking water if even small quantities leak into the ground. Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Uncleaned packaging:****Recommendation:**

Disposal must be made according to official regulations.

Recommended cleansing agents:

Water, if necessary together with cleansing agents.

SECTION 14: Transport information

14.1 UN-Number	UN1950
ADG, IMDG, IATA	UN1950
14.2 UN proper shipping name	
ADG	1950 AEROSOLS
IMDG	AEROSOLS
14.3 Transport hazard class(es)	
Class	2 5F Gases.
Label	2.1
IMDG	
Class	2.1 Gases.
IATA	
Class	2.1 Gases.
Label	2.1
14.4 Packing group	
ADG, IMDG, IATA	Void
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Gases.
Hazard identification number (Kemler code):	-
EMS Number:	F-D,S-U
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADG	
Limited quantities (LQ)	1L
Transport category	2
Tunnel restriction code	D
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1 (8)

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****Australian Inventory of Industrial Chemicals**

67-64-1	Acetone
74-98-6	propane
110-19-0	Isobutyl Acetate

(Contd. on page 5)

Safety Data Sheet

according to WHS Regulations

Date of issue: 03.08.2026

Revised On: 03.08.2026

Trade name: 46-115 GLOSS BLACK

(Contd. of page 4)

106-97-8	n-butane
2807-30-9	Glycol Ether EP
108-10-1	methyl isobutyl ketone
108-65-6	PM acetate
28262-63-7	Acrylic Resin
107-87-9	Methyl Propyl Ketone
64742-47-8	Mineral Spirits
1333-86-4	Carbon black
22464-99-9	solid zirco drier
1330-20-7	xylene (mix)
136-52-7	cobalt bis(2-ethylhexanoate)
64742-88-7	Solvent naphtha (petroleum), medium aliph.
100-41-4	ethyl benzene
64742-89-8	VM&P Naphtha
136-51-6	calcium bis(2-ethylhexanoate)
68953-58-2	Alkyl Quaternary Ammonium Montmorillonite
67-63-0	Isopropyl Alcohol
64742-95-6	Solvent naphtha, light aromatic
8002-43-5	Soya Lecithin
7732-18-5	Water

Standard for the Uniform Scheduling of Medicines and Poisons

67-64-1	Acetone	S5
108-10-1	methyl isobutyl ketone	S5
1330-20-7	xylene (mix)	S6

Australia: Priority Existing Chemicals

None of the ingredients is listed.

Directive 2012/18/EU**Named dangerous substances - ANNEX I****Seveso category****Qualifying quantity (tonnes) for the application of lower-tier requirements**None of the ingredients is listed.
P3a FLAMMABLE AEROSOLS

150 t

Qualifying quantity (tonnes) for the application of upper-tier requirements

500 t

Class	Share in %
NR	39.8

Waterhazard class:

Water hazard class 1 (Self-assessment): slightly hazardous for water.

SECTION 16: Other information**Department issuing SDS:**

Technical Services