

Driven Carb Defender

SDS Number: 64500DCD

Revision Date: 11/23/2022

Page 1 of 4

1

PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

Driven Racing Oil
3416 Democrat Rd.
Memphis, TN 38118

Company Name:

Address:

Telephone/Fax number:

Emergency telephone number:

Nason Engine Parts

Unit 2/5 Monterey Road Dandenong South Vic 3175 AUSTRALIA

Tel: 03 9797 1140

Australia: 1800 862 115

Product Identifier: Driven Carb Defender

SDS Number: 64500DCD

Revision Date: 11/23/2022

CAS Number: Blend

2

HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Physical, Flammable Liquids, 4

Health, Skin corrosion/irritation, 2

Health, Serious Eye Damage/Eye Irritation, 2 A

Health, Carcinogenicity, 2

Health, Specific target organ toxicity - Single exposure, 3

Health, Aspiration hazard, 1

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: DANGER

GHS Hazard Pictograms:



GHS Hazard Statements:

H227 - Combustible liquid

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H351 - Suspected of causing cancer

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

H304 - May be fatal if swallowed and enters airways

GHS Precautionary Statements:

P210 - Keep away from heat/sparks/open flames/hot surfaces. No smoking

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

P302+352 - IF ON SKIN: Wash with soap and water.

P305+351+338 - IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

P304 + P341 - IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

P308 + P313 - IF exposed or concerned: Get medical advice/ attention.

Driven Carb Defender

SDS Number: 64500DCD

Revision Date: 11/23/2022

Page 2 of 4

3 COMPOSITION/INFORMATION OF INGREDIENTS

Chemical Ingredients:		
CAS#	%	Chemical Name:
64742-47-8	45-55%	Distillates, petroleum, hydrotreated light
64742-95-6	25-35%	Solvent naphtha, petroleum, light arom.
*****	25-35%	Monoalkylaryl alkoxyate aminated (proprietary)
95-63-6	<15%	1,2,4-Trimethylbenzene
108-67-8	<10%	1,3,5-Trimethylbenzene
103-65-1	<10%	n-Propyl benzene
1330-20-7	<3%	Xylene
98-82-8	<3%	Cumene
526-73-8	<3%	1,2,3-Trimethylbenzene

4 FIRST AID MEASURES

Inhalation: If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.

Skin Contact: Wash with soap and water. Remove contaminated clothing and wash before reuse. Get medical attention if needed.

Eye Contact: Flush with water for several minutes. If effects occur, consult a physician.

Ingestion: Rinse mouth with water and drink 2-4 cups of water. Get immediate medical attention. Note to Physician: Activated charcoal may be administered.

5 FIRE FIGHTING MEASURES

Flash Point: 65 C (149 F)

Flash Point Method: PMCC

Use dry powder, foam, or carbon dioxide fire extinguishers.

Water may be ineffective unless used by experienced fire fighters.

6 ACCIDENTAL RELEASE MEASURES

Eliminate sources of ignition - Heat, sparks, flame, and electricity

Contain spilled material.

Collect in suitable and properly labeled containers.

Pick up excess with inert absorbent material

Keep away from drains and ground water.

7 HANDLING AND STORAGE

Handling Precautions:

- Avoid contact with eyes, skin, or clothing.
- Keep away from sources of ignition.
- Do not pressurize, cut, weld, braze, solder, drill, or grind containers.
- Handle with care and avoid spillage on the floor (slippage).
- Ground and bond containers when transferring material

Storage Requirements:

- Keep away from sources of ignition.
- Store in a tightly closed container

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

Personal Protective Equipment:

- Hand protection: Chemical resistant gloves are recommended.
- Eye protection: Safety glasses with side shields are recommended.

Driven Carb Defender

SDS Number: 64500DCD

Revision Date: 11/23/2022

Page 3 of 4

Respiratory protection: If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate.

Exposure Guidelines:

Light Aromatic Solvent Naphtha

OSHA TWA: 500 ppm

1,2,4-Trimethylbenzene

ACGIH TWA: 25 ppm

Xylene

OSHA TWA: 100 ppm, 435 mg/m³

ACGIH TWA: 100 ppm, 434 mg/m³

OSHA STEL: 150 ppm, 655 mg/m³

ACGIH STEL: 150 ppm, 651 mg/m³

Cumene

OSHA PEL: 50 ppm

OSHA TWA: 50 ppm, 245 mg/m³

ACGIH TWA: 50 ppm, 246 mg/m³

1,3,5-Trimethylbenzene

ACGIH TWA: 25 ppm

1,2,3-Trimethylbenzene

ACGIH TWA: 25 ppm

9

PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Amber	Odor:	Aromatic
Physical State:	Liquid	Solubility:	Nil in water
Spec Grav./Density:	0.8590 at 60 F (Water = 1)	Freezing/Melting Pt.:	Not available
Viscosity:	Not available	Flash Point:	65 C (149 F)
Boiling Point:	Not available	Vapor Density:	Heavier than air (Air=1)
Flammability:	Not available	Bulk Density:	7.15 lbs/gal at 60 F
Partition Coefficient:	Not available	UFL/LFL:	Not available
Vapor Pressure:	Not available		
pH:	Not available		
Evap. Rate:	Not available		
Decomp Temp:	Not available		

10

STABILITY AND REACTIVITY

Chemical Stability:	Product is stable under normal conditions.
Conditions to Avoid:	High temperatures above 50 C (122 F), sparks, and open flame.
Materials to Avoid:	Avoid strong oxidizing agents. May burn or react violently to flourine/oxygen mixtures.
Hazardous Decomposition:	Combustion will produce carbon dioxide and, possibly toxic chemicals such as carbon monoxide.
Hazardous Polymerization:	Will not occur.

11

TOXICOLOGICAL INFORMATION

Repeated skin contact with this product may cause dermatitis or an oil acne.
No component is listed as mutagen or teratogen.

SKIN EFFECTS:

Solvent Petroleum Naphtha no deaths reported at 4 ml/kg (Rat). Slightly irritating (rabbit, 4 hour(s)).

Monoalkylaryl alkoxylate LD50 >3000 mg/kg in rats

1,2,4-Trimethylbenzene LD50 3160 mg/kg in rabbits

Xylene LD50 >14100 mg/kg in rabbits

Cumene LD50 10578 mg/kg in rabbits

Driven Carb Defender

SDS Number: 64500DCD

Revision Date: 11/23/2022

Page 4 of 4

ACUTE ORAL EFFECTS:

Solvent Petroleum Naphtha LD50 2900 mg/kg in rats.

1,2,4-Trimethylbenzene LD50 5000 mg/kg in rats

1,3,5-Trimethylbenzene LD50 >5000 mg/kg in rats

n-Propylbenzene LD50 6040 mg/kg in rats

Xylene LD50 3523 mg/kg in rats

Cumene LD 50 1400 mg/kg in rats

ACUTE INHALATION EFFECTS:

Solvent Petroleum Naphtha no deaths at 710 ppm in rats (4 Hours)

1,2,4-Trimethylbenzene LC50 18000mg/m³ in rats (4hours)1,3,5-Trimethylbenzene LC50 2400 mg/m³ in rats (4hours)

Xylene LC50 5000 to 8500 ppm in rats (4hours)

Cumene LC50 8000 ppm in rats (4 hours)

12**ECOLOGICAL INFORMATION**

Avoid exposing to the environment, no specific aquatic data available.

13**DISPOSAL CONSIDERATIONS**

Dispose of waste material in accordance with all local, state/provincial, and national requirements

Do not flush to surface water or drains

14**TRANSPORT INFORMATION**

NA1993, Combustible liquid, n.o.s. (Petroleum Naphtha, 1,2,4-Trimethylbenzene), - , III

This material is not regulated for US DOT transportation in quantities less than 119 Gallons.

IMDG: Not regulated

IATA: Not regulated

15**REGULATORY INFORMATION**

COMPONENT (CAS#) [%] - CODES

TSCA: All components listed or exempt

DSL: All components listed or exempt

**WARNING**This product can expose you to chemicals including Cumene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.**REGULATORY KEY DESCRIPTIONS**

TSCA = United States Toxic Substances Control Act

DSL = Canadian Domestic Substances List

16**OTHER INFORMATION**

The information contained in this Safety Data Sheet relates only to the specific material designated. Driven Racing Oil assumes no legal responsibility for use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Driven Racing Oil.

Revision Date: 11/23/2022